

Control unit 230 V for 3RW4436 with screw terminals



product designation	Control unit
Substance Prohibance (Date)	07/01/2006
Certificates/ approvals	
General Product Approval	EMC other

[Confirmation](#)[Confirmation](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4736-6SC44>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4736-6SC44>

Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4736-6SC44>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW4736-6SC44&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4736-6SC44&lang=en)Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current<https://support.industry.siemens.com/cs/ww/en/ps/3RW4736-6SC44/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW4736-6SC44&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

1/18/2021 

