

Firing PCB 460 V for 3RW4446, 3RW4447



product designation	Printed circuit board
Substance Prohibittance (Date)	03/01/2017
Certificates/ approvals	
General Product Approval	EMC other

[Confirmation](#)[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4747-0VC70>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4747-0VC70>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4747-0VC70>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4747-0VC70&lang=enCharacteristic: Tripping characteristics, I^t, Let-through current<https://support.industry.siemens.com/cs/ww/en/ps/3RW4747-0VC70/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW4747-0VC70&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

1/7/2021 

