



Control unit 24 V for 3RW52, Size 1 to 4 Analog output

product designation	Control unit
design of the product	24 V, analog output
manufacturer's article number	
• of soft starter	<a href="#">3RW52...-AC0</a>
Substance Prohibittance (Date)	02/15/2018

<b>Ambient conditions</b>	
ambient temperature during storage	-40 ... +80 °C

<b>Certificates/ approvals</b>			
General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping

[Confirmation](#)

EG-Konf.

[Type Test Certificates/Test Report](#)

ABS

Marine / Shipping

other



LRS



PRS



DNV-GL

[Confirmation](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5920-1UA00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5920-1UA00>

Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5920-1UA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5920-1UA00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5920-1UA00&lang=en)Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current<https://support.industry.siemens.com/cs/ww/en/ps/3RW5920-1UA00/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5920-1UA00&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



last modified:

1/18/2021 

