



Control unit 110-250 V for 3RW55, Size 1 to 4

product designation	Control unit
design of the product	110 ... 250 V
manufacturer's article number	
• of soft starter	3RW551.-.HA1., 3RW552.-.HA1., 3RW553.-.HA1., 3RW554.-.HA1.
Substance Prohibittance (Date)	02/15/2018

<b>Ambient conditions</b>	
ambient temperature during storage	-40 ... +80 °C

<b>Certificates/ approvals</b>			
General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping

[Confirmation](#)


EG-Konf.


[Type Test Certificates/Test Report](#)


ABS

Marine / Shipping	other
-------------------	-------



LRS



PRS



DNV-GL

[Confirmation](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5950-1UY10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5950-1UY10>

Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-1UY10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5950-1UY10&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5950-1UY10&lang=en)
Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current
<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-1UY10/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5950-1UY10&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



last modified:

1/18/2021 

