

Data sheet

3RW5951-1ES04



SIRIUS 3RW55 starter kit including 3RW55 Soft Starter 13 A, 200-480 V, 24 V AC/DC Soft Starter ES V15, 24 V power supply, connecting cable and RJ45 network cable

product brand name	SIRIUS
product designation	starter kit
product type designation	3RW55
manufacturer's article number	
• of soft starter	3RW55
Substance Prohibitation (Date)	02/15/2018

Ambient conditions	
ambient temperature during storage and transport	-40 ... +80 °C

Safety related data	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

Certificates/ approvals		
General Product Approval	Declaration of Conformity	Marine / Shipping

[Confirmation](#)



EG-Konf.



ABS



LRS

Marine / Shipping	other
-------------------	-------



PRS



DNV-GL

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5951-1ES04>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5951-1ES04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5951-1ES04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5951-1ES04&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5951-1ES04/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW59511ES04&objecttype=140&view=detail>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



last modified:

1/12/2021 

