

Bypass kit for 3RW55/52 Size 4, 370 A to 570 A



product designation	Bypass unit
design of the product	370 ... 570 A
manufacturer's article number	3RW5246, 3RW5247, 3RW5248
<ul style="list-style-type: none"> <li>• of soft starter</li> <li>• of soft starter</li> </ul>	3RW5546.-.HA., 3RW5547.-.HA., 3RW5548.-.HA..
Substance Prohibitance (Date)	02/15/2018

Ambient conditions	
ambient temperature during storage	-40 ... +80 °C

Certificates/ approvals			
General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping

[Confirmation](#)


EG-Konf.


[Type Test Certificates/Test Report](#)


ABS

Marine / Shipping	other
-------------------	-------



LRS



PRS



DNV-GL

[Confirmation](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RW5954-0BT00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RW5954-0BT00>

Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5954-0BT00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3RW5954-0BT00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3RW5954-0BT00&lang=en)
Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current
<https://support.industry.siemens.com/cs/ww/en/ps/3RW5954-0BT00/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mfb=3RW5954-0BT00&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



last modified:

1/18/2021 

