



Power semiconductor module 690 V, for 3RW55, 840 A

Figure similar

product designation	Power semiconductor module
design of the product	690 V, 840 A
manufacturer's article number	
• of soft starter	3RW5554-.HA.6 (3x)
Substance Prohibittance (Date)	10/21/2019

Ambient conditions	
ambient temperature during storage	-40 ... +80 °C

Certificates/ approvals			
General Product Approval	Declaration of Conformity	Test Certificates	Marine / Shipping

[Confirmation](#)

EG-Konf.

[Type Test Certificates/Test Report](#)

ABS

Marine / Shipping	other
-------------------	-------



LRS



PRS



DNV-GL

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5955-0SW06>

Cax online generator

<http://support.automation.siemens.com/WWW/CAXorder/default.aspx?lang=en&mlfb=3RW5955-0SW06>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5955-0SW06>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5955-0SW06&lang=enCharacteristic: Tripping characteristics, I²t, Let-through current<https://support.industry.siemens.com/cs/ww/en/ps/3RW5955-0SW06/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5955-0SW06&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



last modified:

1/18/2021 

