



Removable control terminals with spring-type terminals 2 blocks with 6 terminals each

<b>product designation</b>	Removable control terminals
<b>design of the product</b>	With spring-loaded terminals, contains 2 blocks each with 6 terminals
<b>manufacturer's article number</b>	<ul style="list-style-type: none"> <li>• of soft starter</li> <li>• of soft starter</li> <li>• of soft starter</li> </ul>
<b>Substance Prohibitance (Date)</b>	02/15/2018
<b>Ambient conditions</b>	
ambient temperature during storage	-40 ... +80 °C
<b>Certificates/ approvals</b>	
<b>General Product Approval</b>	<b>Declaration of Conformity</b>



[Confirmation](#)



#### Test Certificates

#### Marine / Shipping

[Type Test Certificates/Test Report](#)



#### other

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RW5980-2TR00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5980-2TR00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5980-2TR00>

**Image database (product images, 2D dimension drawings, 3D models, device diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5980-2TR00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5980-2TR00&lang=en)

**Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5980-2TR00/char>

**Characteristic: Installation altitude**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5980-2TR00&objecttype=14&gridview=view1>

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



last modified:

1/18/2021 

